

Legacy Bidder Profile Service

Legacy Bidder Profile Service

Bidder Profiles are used to create and manage filtering criteria for which real-time [Bid Requests](#) you wish to receive. Profiles allow you to limit resources required to process unwanted bid requests. See the [Bidder Profile - FAQ](#).

On This Page:

- [Important Notes](#)
- [Supported Filtering Criteria](#)
- [REST API](#)
- [JSON Fields](#)
 - [Country Targets](#)
 - [Region Targets](#)
 - [City Targets](#)
 - [Examples](#)
- [Related Topics](#)

Important Notes

- For a bid request to pass a bidder profile, the bid request must meet ALL of the specified filter criteria.
- You may create multiple profiles for your bidder, but **only one** parent profile can be **active** for your bidder at any given time. Activate a profile by associating it with your bidder, using the [Bidder Service](#).
- Note that your bidder will always receive bid requests for inventory that is owned by a member associated with your bidder. Bidder profiles are not applied in this case.
- Data Provider bidders can only have one parent profile and no child profiles.

Profiles must be attached to an active bidder object

After you create a profile, you must attach the profile to your bidder by specifying "parent_profile_id" via the [Bidder Service](#)

Do not use deprecated fields

Do not include any of the fields marked as deprecated below when you are configuring your profile(s). This will lead to your bidder not receiving the expected volume of bid requests.

Frequent profile updates may temporarily lock that profile

If you make multiple updates to a bidder profile within 30 minutes, the profile can potentially get locked as a safety precaution. If a profile gets locked, traffic matching only this profile will not go through for approximately 5 minutes.

Supported Filtering Criteria

The following filtering criteria are currently supported:

- **Selling Member**
 - Specify whether to require or exclude inventory from members, see the [Platform Member Service](#)

Please note that the Xandr Direct Seller Member Group is included by default and cannot be excluded via the API or the UI. For more information, see [AppNexus Direct for External Demand Partners](#).

- **Geography**
 - **Country**
 - Include/exclude requests for a specified set of countries, OR
 - Receive bid requests for any countries EXCEPT a specified set of countries
 - **Region**
 - Include/exclude requests for a specified set of regions, OR
 - Receive bid requests for any regions EXCEPT a specified set of regions
 - **DMA**
 - Include/exclude requests for a specified set of DMAs, OR
 - Receive bid requests for any regions EXCEPT a specified set of DMAs
- **Inventory**

- Domain List
 - Include/exclude requests for impressions that meet the requirements of white- or black-lists
- Inventory Attribute
 - Include/exclude requests for impressions that contain certain inventory attributes
- Audit Status
 - Exclude requests from domains that have not been audited by Xandr
- Audience

As of April 27, 2019, Xandr no longer supports segments on the platform for externally integrated DSPs.

- Segment Targeting
 - Include/exclude requests for users that satisfy the segment targeting criteria
- Creative Size
 - Include/exclude bid requests for the specified set of creative sizes
- Supply Type (web / mobile_app / mobile_web)
 - Include/exclude impressions for regular web and mobile apps.

REST API

View Profiles

To see all of the profiles attached to your bidder:

GET https://api.adnxs.com/profile/BIDDER_ID

To see a specific profile attached to your bidder:

GET https://api.adnxs.com/profile/BIDDER_ID/PROFILE_ID

Add a Profile for your bidder

To add a new profile, use the following:

POST https://api.adnxs.com/profile/BIDDER_ID
(profile JSON)

Modify an Existing Profile

To modify an existing profile, use the following:

PUT https://api.adnxs.com/profile/BIDDER_ID/PROFILE_ID
(profile JSON)

Delete an existing profile

To delete a specific profile attached to your bidder:

DELETE https://api.adnxs.com/profile/BIDDER_ID/PROFILE_ID

Note: only inactive profiles can be deleted; that is profiles which are not associated with the bidder object.

Activate a profile for your bidder as the parent profile

Use the [Bidder Service](#) to set the profile_id field on the bidder to the id of the desired bidder profile.

Activate a profile for your bidder as a child profile

Use the [Bidder Service](#) to update the child_profiles array on the bidder to include id of the desired bidder profile.

JSON Fields

Field	Required	Type	Description
ID	yes, on update	String	Unique identifier for the bidder profile
code	no	String	Alternative identifier for the bidder profile, specific to the bidder
description	no	String	Description of the bidder profile
last_activity	no	timestamp	The timestamp of the last modification to the profile
Bid Throttling			

passthrough_percent	no	double	The percent (50 = 50%) of bid requests which satisfy your profile targeting that you wish to receive. Requests that are sent to your bidder are randomly chosen, although you can choose for your bidder to always receive requests for users in segments of members associated with your bidder. If you set passthrough_percent to 0, your bidder will only receive requests for users in at least one of your members' segments. These values take effect in increments of 0.1.
Member Filtering			
member_targets	no	Array of Objects	Array of objects that include the member ids of members. The default action, if no action is specified, is "include" - meaning the member IDs must be included. This may be overridden by specifying an "action" in the object, e.g. "member_targets":[{"id":"100","action": "exclude"}]. See Platform Member Service for more details.
Geography Filtering			
country_action	no	Enum - "exclude" or "include"	If "exclude", only bid requests for countries NOT in "country_targets" will be sent to the bidder. If "include", only bid requests for countries in "country_targets" will be sent to the bidder. Default is exclude.
country_targets	no	Array of Objects	The country IDs to be either excluded or included, as defined by the <code>country_action</code> field. You can use the Country Service to retrieve a list of country IDs. See Country Targets for more details and format.
region_action	no	Enum - "exclude" or "include"	If "exclude", only bid requests for regions NOT in "region_targets" will be sent to the bidder. If "include", only bid requests for regions in "region_targets" will be sent to the bidder. Default is exclude.
region_targets	no	Array of Objects	The region/state IDs to be either excluded or included, as defined by the <code>region_action</code> field. You can use the Region Service to retrieve a list of region IDs. See Region Targets for more details and format.
dma_targets	no	Array of Objects	Array of objects specifying the dmAs to be targeted (for inclusion or exclusion). E.g. [{"dma":123}, {"dma":124}]
dma_action	no	Enum - "exclude" or "include"	Defaults to "exclude". See <code>dma_targets</code>
city_targets	no	Array of Objects	The IDs of cities to be either included or excluded, as defined by the <code>city_action</code> field. You can use the City Service to retrieve a list of city IDs. See City Targets for more details and format.
city_action	no	Enum - "exclude" or "include"	If "exclude", only bid requests for cities NOT in "city_targets" will be sent to the bidder. If "include", only bid requests for cities in "city_targets" will be sent to the bidder. Default is exclude.
Inventory			
inventory_action	no	Enum - "exclude" or "include"	Deprecated. Please leave it as "exclude" and don't use this field, as this can reduce the available inventory sent to your bidder.
use_inventory_attribute_targets	no	Boolean	If set to "true", then <code>inventory_attribute_targets</code> will be applied. This flag allows you to "opt-in" to receive certain inventory attributes, such as toolbars, if they exist for a piece of inventory. If "false", the bidder will receive all inventory.
inventory_attribute_targets	no	Array of inventory attribute objects	An array of objects for the targets to include, e.g. [{"id":12}]. If <code>use_inventory_attribute_targets</code> is enabled, we will send bid requests that contain the selected attributes. We will also send bid requests that contain no inventory attributes. To exclude a particular inventory attribute, simply include all the IDs except for the attribute you wish to exclude.
non_audited_url_action	No	string	If this is set to "exclude", all inventory that has not been audited by Xandr will be excluded. Otherwise, all inventory will be included.
domain_list_action	no	Enum - "exclude" or "include"	Default action to apply to <code>domain_list_target</code> .
domain_list_targets	no	Array of objects with the ID of the domain lists	Array of objects for the domain list targets, e.g. []. Only bid requests for inventory that match the <code>domain_list_action</code> for the enumerated domain lists will be sent to the bidder.
domain_action	<i>deprecated</i>		
domain_targets	<i>deprecated</i>		
Audience			

segment_targets	no	Array of segment targets with the ID and action for each.	<p>If "segment_boolean_operator" is "and", then if "action" for a segment is set to "exclude", then impressions for users that are in that segment not be sent to the bidder; if any "action" is set to "include", then users in the segments being included will be sent to the bidder. If "segment_boolean_operator" is set to "or", then users that meet any of the segment_targets criteria will be sent to the bidder.</p> <div style="border: 1px solid red; padding: 5px; text-align: center;"> <p>As of April 27, 2019, Xandr will no longer support segments on the platform for externally integrated DSPs.</p> </div>
segment_boolean_operator	no	Enum - "and" or "or"	<p>Action to apply to the segment_targets. "And" means all of the criteria must be satisfied. "Or" means at least one must be met.</p> <div style="border: 1px solid red; padding: 5px; text-align: center;"> <p>As of April 27, 2019, Xandr will no longer support segments on the platform for externally integrated DSPs.</p> </div>
Supply Type (web / mobile)			
supply_type_targets	no	Array of supply type targets: "mobile_app" (for mobile app inventory), "mobile_web" (for mobile web inventory), "web" (for regular display inventory)	Determines which supply type targets should be included or excluded pursuant to supply_type_action
supply_type_action	no	Enum - "exclude" or "include"	Action to apply to supply_type_targets
Mobile-Specific			
carrier_targets	no	<i>Not yet supported</i>	
carrier_action	no	Enum - "exclude" or "include"	Action to apply to carrier_targets
handset_make_targets	no	<i>Not yet supported</i>	
handset_make_action	no	Enum - "exclude" or "include"	Action to apply to handset_make_targets
handset_model_targets	no	<i>Not yet supported</i>	
handset_model_action	no	Enum - "exclude" or "include"	Action to apply to handset_model_targets
location_target_radius	no	<i>Not yet supported</i>	
location_target_latitude	no	<i>Not yet supported</i>	
location_target_longitude	no	<i>Not yet supported</i>	
Other			
size_targets	no	Array of Objects	Array of widths and heights, specifying creative sizes that your bidder will bid on. E.g. [{"width":300,"height":250},{width":600,"height":160}]
Not Currently Supported			
language_targets			This field is not currently available

postal_code_targets			This field is not currently available
age_targets			This field is not currently available
daypart_targets			This field is not currently available
browser_targets			This field is not currently available

Country Targets

Each object in the `country_targets` array contains the following fields.

Field	Type	Description
id	int	The ID of the country. You can use the Country Service to retrieve a complete list of country IDs.
name	string	Read-only. The name of the country.
code	string	Read-only. The code for the country.

Example

```
{
  "profile": {
    "country_action": "include",
    "country_targets": [
      {
        "id": 233,
        "name": "United States",
        "code": "US"
      }
    ]
  }
}
```

Region Targets

Each object in the `region_targets` array contains the following fields.

Field	Type	Description
id	int	The ID of the region. You can use the Region Service to retrieve a list of region IDs.
name	string	Read-only. The name of the region.
code	string	Read-only. The code for the region.
country_name	string	Read-only. The name of the country to which the region belongs.
country_code	string	Read-only. The code for the country to which the region belongs.

Example

```

{
  "profile": {
    "region_action": "include",
    "region_targets": [
      {
        "id": 1
      }
    ]
  }
}

```

City Targets

Each object in the `city_targets` array contains the following fields.

Field	Type	Description
id	int	The ID of the city to target. You can use the City Service to retrieve a list of city IDs.
name	string	Read-only. The name of the city to target.
region_name	string	Read-only. The name of the region to which the city belongs.
region_code	string	Read-only. The code of the region to which the city belongs.
country_name	enum	Read-only. The name of the country to which the region belongs.
country_code	enum	Read-only. The code of the country to which the region belongs.

Example

```

{
  "profile": {
    "city_action": "include",
    "city_targets": [
      {
        "id": 123,
        "name": "Queens",
        "region_name": "New York",
        "region_code": "NY",
        "country_code": "US",
        "country_name": "United States",
      }
    ]
  }
}

```

Examples

Authentication Token

Authentication is always the first step when using the API Services. The authentication token can then be written to our cookie file for future use. Please see [Authentication Service](#) for more detailed instructions.

>> Add a new profile to bidder 6. The ID of the new profile is 123

```
$ cat bidder_profile:

{
  "profile":
  {
    "description": "Only Alberta (NO US can be included)",
    "country_action": "include",
    "country_targets": [{"id": 1}, {"id": 2}],
    "region_action": "exclude",
    "region_targets": [{"id": 1}],
    "member_targets": [
      {
        "id": "100",
        "action": "exclude"
      },
      {
        "id": "102",
        "action": "exclude",
        "name": "Inventory name 2"
      }
    ],
    "dma_targets": [{"dma": 123}, {"dma": 124}],
    "dma_action": "exclude",
    "segment_boolean_operator": "and",
    "segment_targets": [
      {
        "id": "16808",
        "name": "Users meeting certain criteria",
        "action": "include",
        "start_minutes": null,
        "expire_minutes": null,
        "other_less": null,
        "other_greater": null,
        "other_equals": null
      },
      {
        "id": "16809",
        "name": "Users that have seen an ad for this campaign and should not be
targeted for 2 days",
        "action": "exclude",
        "start_minutes": null,
        "expire_minutes": "2880",
        "other_less": null,
        "other_greater": null,
        "other_equals": null,
      }
    ],
    "size_targets": [{"width": 300, "height": 250}, {"width": 600, "height": 160}]
  }
}

$ curl -b cookies -c cookies -X POST --data-binary @bidder_profile
"https://api.adnxs.com/profile/6"

{
  "response":
  {
```

```
"status": "OK",  
"id": "123"
```

```
}  
}
```

>> See all profiles currently associated with bidder 6

```
$ curl -b cookies -c cookies "https://api.adnxs.com/profile/6"
```

- See profile 123 associated with bidder 6:

```
$ curl -b cookies -c cookies "https://api.adnxs.com/profile/6/123"
```

- To activate a profile for your bidder, use the [Bidder Service](#) to set the profile_id field on the bidder to the id of the desired bidder profile.

>> To update profile ID 123 on bidder 6

```
$ cat bidder_profile:  
  
  {  
    "profile":  
  {  
    "id": "123",  
    "country_action": "include",  
    "country_targets": [{"id": 233}]  
  }  
  }  
  
$ curl -b cookies -c cookies -X PUT --data-binary @bidder_profile  
"https://api.adnxs.com/profile/6/123"
```

>> Add a domain list to your bidder profile as a "blacklist"

For more information about domain lists, see the [Domain List Service](#).

```
$ cat domain-list-profile  
{  
  "profile" : {  
    "domain_list_targets" : [  
      {  
        "id" : 9351  
      }  
    ],  
    "domain_list_action" : "exclude",  
    "id" : 431739  
  }  
}  
  
$ curl -b cookies -c cookies -X PUT --data-binary @domain-list-profile  
'https://api.adnxs.com/profile/497/431739'
```

```
{
  "response" : {
    "count" : 1,
    "num_elements" : null,
    "id" : "431739",
    "profile" : {
      "supply_type_targets" : null,
      "browser_targets" : null,
      "id" : 431739,
      "dma_targets" : null,
      "screen_size_targets" : null,
      "inventory_attribute_targets" : null,
      "device_type_targets" : null,
      "dma_action" : "exclude",
      "operating_system_targets" : null,
      "domain_list_targets" : [
        {
          "id" : 9351,
          "deleted" : false,
          "type" : "black",
          "description" : "Rich's awesome domain list (blacklist)",
          "name" : "Rich's awesome domain list (blacklist)"
        }
      ],
      "session_freq_type" : "platform",
      "operating_system_family_targets" : null,
      "domain_targets" : null,
      "venue_targets" : null,
      "description" : "Ethical Ad Blocker Test Segment",
      "city_targets" : null,
      "age_targets" : null,
      "domain_action" : "exclude",
      "inventory_action" : "exclude",
      "site_targets" : null,
      "size_targets" : [
        {
          "width" : 300,
          "height" : 50
        },
        {
          "width" : 300,
          "height" : 250
        }
      ],
      "location_target_radius" : null,
      "language_action" : "exclude",
      "ip_targets" : null,
      "segment_targets" : [
        {
          "deleted" : false,
          "other_greater" : null,
          "name" : "ethical ad blocker segment 00",
          "code" : "ethical-adblock-00",
          "other_less" : null,
          "expire_minutes" : null,
          "action" : "include",
          "other_in_list" : null,
          "id" : 110944,

```

```
        "other_equals" : null,
        "start_minutes" : null
    }
],
"is_expired" : false,
"region_action" : "exclude",
"location_target_latitude" : null,
"code" : "ethical-adblock-00",
"inventory_group_targets" : null,
"country_action" : "exclude",
"querystring_targets" : null,
"carrier_targets" : null,
"member_id" : null,
"passthrough_percent" : 100,
"segment_boolean_operator" : "or",
"intended_audience_targets" : null,
"operating_system_extended_targets" : null,
"device_model_action" : "exclude",
"language_targets" : null,
"gender_targets" : null,
"non_audited_url_action" : "include",
"inventory_network_resold_targets" : null,
"supply_type_action" : "exclude",
"daypart_targets" : null,
"daypart_timezone" : null,
"postal_code_targets" : null,
"querystring_boolean_operator" : "and",
"last_activity" : "2015-03-30 21:25:41",
"member_targets" : [
    {
        "action" : "include",
        "billing_name" : "unexposed",
        "id" : 4782,
        "third_party_auditor_id" : null
    }
],
"browser_family_targets" : null,
"screen_size_action" : "exclude",
"min_sessionimps" : null,
"device_model_targets" : null,
"querystring_action" : "exclude",
"segment_group_targets" : null,
"country_targets" : null,
"city_action" : "exclude",
"domain_list_action" : "exclude",
"location_target_longitude" : null,
"carrier_action" : "exclude",
"position_targets" : null,
"use_inventory_attribute_targets" : false,
"device_type_action" : "exclude",
"region_targets" : null,
"browser_action" : "exclude"
},
"start_element" : null,
"status" : "OK"
```

```
}  
}
```

Related Topics

- [Bidder Profile - FAQ](#)
- [Bidder Profile Editor in the UI](#)
- [Configure your Profile](#)